

Bounds and Constructions for Granular Media Coding

Artyom Sharov, Ronny Roth

Department of Computer Science

Technion – Israel Institute of Technology

Combinatorial model

- $[s] = \{0, 1, \dots, s-1\}$
- An alphabet $\Sigma = [q]$
- A *grain* (of length 2) ending at location $e \in [n] \setminus \{0\}$ in a word $\mathbf{x} = (x_i)_{i \in [n]}$ smears the value of cell $e-1$ to cell e : $x_e \leftarrow x_{e-1}$
- A *grain pattern* $\mathcal{S} \subseteq [n] \setminus \{0\}$ contains all the grain locations and inflicts errors to \mathbf{x} by means of operator $\sigma_{\mathcal{S}}$

Example

- $\Sigma = [3]$, $n = 6$, $\mathbf{x} = 102022$, $S = \{1, 3, 5\}$ and $S' = \{1, 2\}$

\mathbf{x} :

1	0	2	0	2	2
---	---	---	---	---	---

\mathbf{x} :

1	0	2	0	2	2
---	---	---	---	---	---



S :

1	0	2	0	2	2
---	---	---	---	---	---

S' :

1	0	2	0	2	2
---	---	---	---	---	---



$\sigma_S(\mathbf{x})$:

1	1	2	2	2	2
---	---	---	---	---	---

$\sigma_{S'}(\mathbf{x})$:

1	1	0	0	2	2
---	---	---	---	---	---

Applications

- Conventional magnetic recording media: *grains*
- Wood *et al.* suggested a new approach for magnetizing areas as small as a single grain
- Mazumdar *et al.* considered a 1-D combinatorial error model with specific substitution errors and grains of length 1 and 2
- Related to bit-patterned media recording (Iyengar *et al.*)
- S has *overlaps* if there exist $e, e' \in S$ such that $e' = e+1$; otherwise S is *nonoverlapping*

Combinatorial model (cont.)

- Words $\mathbf{x}, \mathbf{y} \in \Sigma^n$ are *t-confusable* if there exist S, S' of size t at most for which $\sigma_S(\mathbf{x}) = \sigma_{S'}(\mathbf{y})$
- A code $\mathcal{C} \subseteq \Sigma^n$ is *t-grain-correcting* if no two distinct codewords are *t-confusable*
- The largest size $M_q(n, t)$
- The *rate* $R_q(\tau) = \limsup_{n \rightarrow \infty} \frac{1}{n} \log_q M_q(n, t)$
- Asymmetry: 111 is 1-confusable with 3 words, whereas 101 is 1-confusable with 4 words

Lower bound on $M_q(n, t)$

- The number $W_t(\mathcal{X})$ of ordered pairs of t -confusable words in \mathcal{X}


Lemma. *Let n, t be positive integers and let $\mathcal{X} \subseteq \Sigma^n$, then*

$$M_q(n, t) \geq \frac{|\mathcal{X}|^2}{4W_t(\mathcal{X})}.$$

- We will evaluate $W_t(\mathcal{X})$ for certain sets \mathcal{X} with prescribed empirical distribution of transitions


Graph $\mathcal{G}(\mathcal{N}) = (V(\mathcal{N}), E(\mathcal{N}))$

- Set of states $V(\mathcal{N}) = V_0 \cup V_1 \cup V_2$ where $V_0 = \{aa : a \in \Sigma\}$, $V_1 = \{a\bar{b} : ab \in \Sigma^2, a \neq b\}$ and $V_2 = \{\bar{a}\bar{b} : ab \in \Sigma^2, a \neq b\}$
- For $q = 2$, $V_0 = \{00, 11\}$, $V_1 = \{\bar{0}1, 0\bar{1}, \bar{1}0, 1\bar{0}\}$, $V_2 = \{0\bar{1}, \bar{1}0\}$
- There is an edge in $E(\mathcal{N})$ from v to v' :



Example

- $\Sigma = [3]$, $n = 6$, $\gamma = (v_i)_{i \in [n]} = 11 \quad 22 \quad 2\bar{0} \quad \bar{1}2 \quad 00 \quad \bar{1}\bar{2}$



- The patterns $S = \{3, 5\}$ and $S' = \{2, 5\}$ make $\mathbf{x} = 122101$ (the left path) and $\mathbf{y} = 120202$ (the right path) confusable

Adjacency matrix $A_G^{(\mathcal{N})}$ for $q = 2$

$$A_G^{(\mathcal{N})} = \begin{array}{c|cccccc} & 00 & \bar{0}1 & 0\bar{1} & \bar{1}0 & 1\bar{0} & 11 \\ \hline 00 & 1 & 0 & 1 & 1 & 0 & 1 \\ \bar{0}1 & 1 & 0 & 0 & 0 & 1 & 1 \\ 0\bar{1} & 1 & 0 & 0 & 1 & 0 & 1 \\ \bar{1}0 & 1 & 0 & 1 & 0 & 0 & 1 \\ 1\bar{0} & 1 & 1 & 0 & 0 & 0 & 1 \\ 11 & 1 & 1 & 0 & 0 & 1 & 1 \end{array}$$


Correspondence between pairs of words and paths

Lemma. For each t -confusable (ordered) pair $(\mathbf{x}, \mathbf{y}) \in \Sigma^n \times \Sigma^n$ there is at least one path $\gamma = (v_i)_{i \in [n]} = (\ell_i r_i)_{i \in [n]}$ in $\mathcal{G}(\mathcal{N})$ such that

1. $v_0 \in V_0$,
2. $\mathbf{x} = (\partial(\ell_i))_{i \in [n]}$,
3. $\mathbf{y} = (\partial(r_i))_{i \in [n]}$ and
4. The total number of bars in γ is at most $2t$.

Function $f(\mathcal{N})$

- Function $f^{(\mathcal{N})} : E^{(\mathcal{N})} \rightarrow [3]^2$
- For an edge $\mathbf{e} = (\ell_{rr}, \ell'_{r'}) \in E^{(\mathcal{N})}$, $f^{(\mathcal{N})}(\mathbf{e}) = (\nu(\mathbf{e}), \chi(\mathbf{e}))$
- $\nu(\mathbf{e})$ counts the smallest number of grains confusing ℓ' and r' ;
- $\chi(\mathbf{e})$ counts the number of crossovers



Matrix function $A_G^{(\mathcal{N})}$

- $[A_G^{(\mathcal{N})}(z, h)]_{v, v' \in V} = \begin{cases} z^{\nu(\mathbf{e})} h^{\chi(\mathbf{e})} & \mathbf{e} = (v, v') \in E(\mathcal{N}) \\ 0 & \text{otherwise} \end{cases}$
- For $q = 2$,

$$A_G^{(\mathcal{N})}(z, h) = \begin{array}{c|cccccc} & 00 & \bar{0}1 & 0\bar{1} & \bar{1}0 & 1\bar{0} & 11 \\ \hline 00 & 1 & 0 & hz & hz & 0 & h^2 \\ \bar{0}1 & h & 0 & 0 & 0 & h^2z & h \\ 0\bar{1} & h & 0 & 0 & h^2z & 0 & h \\ \bar{1}0 & h & 0 & h^2z & 0 & 0 & h \\ 1\bar{0} & h & h^2z & 0 & 0 & 0 & h \\ 11 & h^2 & hz & 0 & 0 & hz & 1 \end{array}$$

Main theorem

- Applying special cases of lemmas from [MR92]: optimizing convex functions subject to linear equality and inequality constraints
- Asymptotic upper bound on the number of paths with average number of crossovers $\sim 2p$ and number of confusing grains $\leq 2\tau$

$$K^{(\mathcal{N})} = \inf_{z \in (0,1], h \in (0,\infty)} \{ \log_q \lambda(A_G^{(\mathcal{N})}(z, h)) - 2\tau \log_q z - 2p \log_q h \}$$

Theorem. *Let $\tau \in (0, 1)$, then^a*

$$R_q(\tau) \geq \varrho_q^{(\mathcal{N})}(\tau) = \sup_{p \in [0,1]} \{ 2H_q(p) - K^{(\mathcal{N})} \}$$

^aAsymptotic version of $M_q(n, t) \geq \frac{|\mathcal{X}|^2}{4W_t(\mathcal{X})}$

Merging states of $G^{(N)}$

- Similar to the standard procedure for reducing the number of states in a presentation of a constrained system while preserving its spectral radius
- The states of V_0 can be merged into superstate 0, V_1 — into superstate 1, V_2 — into superstate 2
- Reduced matrix $A_G^{(N)}$:

$$A_G^{(N)} = \begin{array}{c|ccc} & 0 & 1 & 2 \\ \hline 0 & 1+(q-1)h^2 & 2(q-1)hz & (q-1)(q-2)h^2z^2 \\ 1 & 2h+(q-2)h^2 & (q-1)h^2z & 0 \\ 2 & 2h+(q-2)h^2 & 0 & 0 \end{array}$$

Overlaps allowed


$$[A_g^{(\mathcal{O})}(z, h, m)]_{v, v' \in V} = \begin{cases} z^{\omega(\mathbf{e})} h^{\chi(\mathbf{e})} m^{\mu(\mathbf{e})} & \mathbf{e} = (v, v') \in E^{(\mathcal{O})} \\ 0 & \text{otherwise} \end{cases}$$

$$K^{(\mathcal{O})} = \sup_{0 \leq \eta \leq 2\tau} \inf_{z \in (0, 1], h, m \in (0, \infty)} \{ \log_q \lambda(A_g^{(\mathcal{O})}(z, h, m)) - (2\tau - \eta) \log_q z - \eta \log_q m - 2p \log_q h \}$$

Lower bound on the rate $\varrho_q^{(\mathcal{O})}(\tau) = \sup_{p \in [0, 1]} \{ 2H_q(p) - K^{(\mathcal{O})} \}$

	0	1
$A_g^{(\mathcal{O})} = 0$	$1 + (q-1)h^2$	$2(q-1)hz + (q-1)(q-2)h^2z^2$
1	$2h + (q-2)h^2$	$h^2m + 2(q-2)h^2z$

Lower bounds $\varrho_q^{(j)}(\tau)$



Bounds $\varrho_{1024}^{(TVZ)}(\tau)$ and $\varrho_{16}^*(\tau)$ rely on the code

$$\mathcal{C}^* = \{ \mathbf{c} = (c_i)_{i \in [n]} \in \Sigma^n : c_i \neq c_{i+1} \text{ for any } i \in [n-1] \}$$

Upper bound

- \mathcal{C} is a binary t -grain-correcting code of length n
- Set $\mathcal{B}_t(\mathbf{x})$ of all words $\mathbf{w} \in [2]^n$ for which there is S of size t at most such that $\sigma_S(\mathbf{x}) = \mathbf{w}$
- Lower bound $\psi_t(r)$ on $|\mathcal{B}_t(\mathbf{c})|$ that depends only on the number of runs $r = r(\mathbf{c})$ in \mathbf{c} ; $N(r)$ is the number of words with r runs
- By sphere-packing arguments,

$$\Psi = \sum_{\mathbf{c} \in \mathcal{C}} \psi_t(r(\mathbf{c})) \leq \sum_{\mathbf{c} \in \mathcal{C}} |\mathcal{B}_t(\mathbf{c})| \leq 2^n$$

- $|\mathcal{C}| \leq \sum_{r=1}^{\rho} N(r) + \left\lfloor \frac{\Psi - \sum_{r=1}^{\rho} N(r) \psi_t(r)}{\psi_t(\rho+1)} \right\rfloor$ where ρ is the largest such that $\sum_{r=1}^{\rho} N(r) \psi_t(r) \leq 2^n$

Upper bound (cont.)

- Lower bounds on $|\mathcal{B}_t(\mathbf{c})|$ without overlaps

$$\psi_t^{(\mathcal{N})}(r) = 1 + \sum_{s=1}^{\min\{t, \lfloor (r-1)/3 \rfloor\}} \frac{1}{s!} \prod_{s'=0}^{s-1} (r-1-3s');$$

with overlaps


$$\psi_t^{(\mathcal{O})}(r) = \sum_{s=0}^{\min\{t, r-1\}} \binom{r-1}{s}$$

Theorem. *Let \mathcal{C} be a binary t -grain-correcting code of length n , then $|\mathcal{C}| \leq \Delta^{(j)}(n, t)$ for $j \in \{\mathcal{N}, \mathcal{O}\}$ where*

$$\Delta^{(j)}(n, t) = 2 \sum_{r=1}^{\rho} \binom{n-1}{r-1} + \left\lfloor \frac{2^n - 2 \sum_{r=1}^{\rho} \binom{n-1}{r-1} \psi_t^{(j)}(r)}{\psi_t^{(j)}(\rho+1)} \right\rfloor$$

Upper bounds $\Delta^{(j)}(\tau)$

$n = 200, t \in \{1, 2, \dots, 16\}, \tau = t/n, \Delta^{(j)}(\tau) = \Delta^{(j)}(n, \tau n)$



Asymptotically, $\Delta^{(\mathcal{N})}(\tau)$ and $\Delta^{(\text{MBK})}(\tau)$ are the same; $\Delta^{(\emptyset)}(\tau)$ grows like $H_2(x)$ where x is the smallest positive solution of $H_2(x) + x \cdot H_2(\tau/x) = 1$

Constructions of grain-correcting codes

Theorem (due to Mazumdar *et al.*). For any $n \in \mathbb{Z}^+$,

$$M_2(n, \lfloor n/2 \rfloor) = 2^{\lceil n/2 \rceil}$$

For even n ,

$$\mathcal{C}_n = \{ \mathbf{c} = (c_i)_{i \in [n]} : c_{2s} = c_{2s+1} \text{ for any } s \in [n/2] \}$$

For odd n , $\mathcal{C}_n = (0 \mid \mathcal{C}_{n-1}) \cup (1 \mid \mathcal{C}_{n-1})$

Theorem. For odd n , the above code is the only binary $\lfloor n/2 \rfloor$ -grain-correcting code of length n and size $2^{\lceil n/2 \rceil}$.

Constructions of grain-correcting codes (cont.)

Theorem. *Let $n \geq 5$ be an odd integer. Then*

$$M_2(n, \lfloor n/2 \rfloor - 1) = 2^{\lceil n/2 \rceil}.$$

Theorem. *Let $n \geq 4$ be an even integer. Then*

$$M_2(n, n/2 - 1) = 2^{n/2} + 2.$$

Theorem. *Let $m \geq 2$ be an integer and let $n = 2^m - 1$. Then*

$$M_2(n, 1) \geq 2^{n-m} + 2^{(n-1)/2}.$$

Sizes $M_2(n, t)$ of largest t -grain-correcting codes of length n

$t \backslash n$	2	3	4	5	6	7	8	9
1	2	4	6	8	16	26*	44	
2			4	8	10	16	22	
3					8	16	18	32